

Note: The following is an example of the connections between DT018ATFT and a Microcontroller for 3 Wire SPI			
Value	DT018ATFT Pin	DT018ATFT Desc	Microcontroller 3-wire SPI
	45	NC	
	44	NC	
	43	NC	
	42	NC	
VDD (3.3V)	41	VDDIO	
GND	40	GND	
GND	39	VS	
GND	38	HS	
GND	37	DE	
GND	36	PCLK	
	35	WR	
	34	CS	CS
	33	RES	Reset
	32	TE	
	31	DB0	Data
GND	30	DB1	
GND	29	DB2	
GND	28	DB3	
GND	27	DB4	
GND	26	DB5	
GND	25	DB6	
GND	24	DB7	
GND	23	DB8	
GND	22	DB9	
GND	21	DB10	
GND	20	DB11	
GND	19	DB12	
GND	18	DB13	
GND	17	DB14	
GND	16	DB15	
GND	15	DB16	
GND	14	DB17	
	13	RS	Clock
GND	12	RD	
GND	11	GND	
VDD (3.3V)	10	VCC	
GND	9	SDA	
GND	8	RCM1	
GND	7	RCM0	
GND	6	IM2	
GND	5	IM1	
GND	4	IM0	
	3	LED K2	PWM (Or Quick Test to 130 ohm resistor to GND)
	2	LED K1	PWM (Or Quick Test to 130 ohm resistor to GND)
VDD (3.3V)	1	LEDA	